THESE PLANS ARE TO BE VERIFIED BY A STRUCTURAL ENGINEER ENGINEER'S DRAWINGS SHALL TAKE PRECEDENCE OVER ANY NOTES IN THESE PLANS MANUFACTURER'S INSTALLATION INSTRUCTIONS SHALL TAKE PRECEDENCE OVER ANY NOTES IN THESE

BUILDING PLANNING NOTES

SITE ADDRESS SHALL BE PROVIDED IN A POSITION THAT IS PLAINLY VISIBLE AND LEGIBLE FROM STREET CONSTRUCTION, PROJECTIONS, OPENINGS AND PENETRATION OF EXTERIOR WALLS SHALL COMPLY W TABLE R302.1(1) - REVIEW FIRE RESISTANT CONSTRUCTION IF LESS THAN 5' SEPARATION BETWEEN

ALL HABITABLE ROOMS SHALL HAVE EXTERIOR GLAZING NOT LESS THAN 8% OF THEIR FLOOR AREA TO

PROVIDE NATURAL LIGHT, OR THEY SHALL BE PROVIDED WITH ARTIFICIAL LIGHT ALL HABITABLE ROOMS SHALL BE PROVIDED WITH NATURAL VENTILATION THROUGH OPENINGS TO THE OUTDOOR AIR IN ACCORDANCE WITH SECTION R303, OR THEY SHALL BE PROVIDED WITH MECHANICAL

LIGHT & VENTILATION FOR BATHROOMS, WCs AND SIMILAR ROOMS SHALL COMPLY WITH SECTION R303.3 OUTDOOR AIR INTAKE OPENINGS SHALL BE LOCATED AT LEAST 10' FROM ANY HAZARDOUS OR NOXIOUS

OUTSIDE EXHAUST OPENINGS SHALL BE LOCATED SO AS TO NOT CREATE A NUISANCE AND SHALL NOT BE DIRECTED ONTO WALKWAYS NOR PORCHES

DWELLING SHALL BE PROVIDED WITH HEATING FACILITIES THAT WILL MAINTAIN A TEMPERATURE OF 68°F AT 3' ABOVE THE FLOOR AND 2' FROM EXTERIOR WALLS IN ALL HABITABLE ROOMS THE MIN. CEILING HEIGHT FOR HABITABLE ROOMS, HALLWAYS, CORRIDORS, BATHROOMS, WCs, LAUNDRY

ROOMS & BASEMENTS SHALL NOT BE LESS THAN 7' SANITATION, TOILET, BATH & SHOWER SPACES PER SECTIONS R306 & R307 - 21" CLEARANCE IN FRONT OF FIXTURES

SAFETY GLAZING SHALL BE IN ACCORDANCE WITH SECTION R308 PERMITTED OPENINGS BETWEEN THE GARAGE AND THE DWELLING SHALL BE EQUIPPED WITH 1 3/4" THICK

SOLID WOOD DOORS, HONEYCOMB CORE STEEL DOORS, OR 20 MINUTE FIRE-RATED DOORS ANY GARAGE SHALL BE SEPARATED FROM THE DWELLING & ATTIC AREA IN ACCORDANCE WITH SECTION

GARAGE FLOOR SURFACES SHALL BE SLOPED TO A DRAIN TOWARD THE VEHICLE ENTRY POINT EVERY SLEEPING ROOM SHALL HAVE OPERABLE EMERGENCY ESCAPE AND RESCUE OPENINGS PER

ALL EMERGENCY AND RESCUE OPENINGS SHALL HAVE A MIN. CLEAR OPENING OF 5.7sqft WITH A MIN. NET CLEAR OPENING HEIGHT OF 24" AND WIDTH OF 20" - NO HIGHER THAN 44" AFF STAIRWAYS SHALL HAVE A MIN. HEADROOM HEIGHT OF 80"

STAIRWAYS SHALL HAVE A MINIMUM CLEAR WIDTH OF 31 1/2" AT AND BELOW THE HANDRAIL WHERE ONLY ONE HANDRAIL IS PROVIDED OR 27" WHERE HANDRAILS ARE PROVIDED ON BOTH SIDES A FLIGHT OF STAIRS SHALL HAVE NO MORE THAN 147" OF VERTICAL RISE BETWEEN FLOORS OR

STAIRMELLS TREADS SHALL BE AT LEAST 10" DEEP AND SHALL NOT EXCEED MORE THAN 3/8" VARIATION FROM LARGEST TO SMALLEST TREAD; RISERS SHALL BE NOT GREATER THAN 7-3/4" IN HEIGHT AND SHALL

NOT EXCEED 3/8" IN ANY FLIGHT OF STAIRS - SEE R311.7 A CONTINUOUS HANDRAIL SHALL BE PROVIDED ON AT LEAST ONE SIDE OF THE STAIRWAY - THE TOP OF THE HANDRAILS SHALL BE PLACED NOT LESS THAN 34" AND NOT MORE THAN 38" ABOVE THE NOSING OF

GUARDS AT LEAST 36" IN HEIGHT SHALL BE PROVIDED WHERE PORCHES, BALCONIES OR RAISED FLOOR SURFACES ARE GREATER THAN 30" - GUARDS SHALL NOT HAVE OPENINGS THAT ALLOW PASSAGE OF A

SPHERE 4" IN DIAMETER SMOKE ALARMS SHALL BE INSTALLED PER SECTION R314 IN THE FOLLOWING LOCATIONS: - IN EACH SLEEPING ROOM

- OUTSIDE EACH SEPARATE SLEEPING AREA IN THE IMMEDIATE VICINITY OF THE BEDROOMS - ON EACH ADDITIONAL STORY OF THE DWELLING, INCLUDING BASEMENTS AND HABITABLE ATTICS, BUT

BUT NOT INCLUDING CRAWL SPACES AND UNINHABITABLE ATTICS - SMOKE ALARMS SHALL BE INTERCONNECTED AS INDICATED IN SECTION R314.4

- THE POWER SOURCE FOR SMOKE ALARMS SHALL COMPLY WITH SECTION R314.6 PROTECTION OF WOOD FROM DECAY SHALL BE PROVIDED IN THE FOLLOWING LOCATIONS BY THE USE OF NATURALLY DURABLE WOOD OR WOOD THAT IS PRESERVATIVE-TREATED:

- WOOD JOISTS OR FLOORS LESS THAN 18" OR WOOD GIRDERS LESS THAN 12" FROM EXPOSED GROUND IN CRAWL SPACES OR UNEXCAVATED AREAS WITHIN THE BUILDING FOUNDATION - FLOOR FRAMING MEMBERS THAT REST ON CONCRETE OR MASONRY EXTERIOR WALLS AND ARE LESS

- SILLS AND SLEEPERS ON A CONCRETE OR MASONRY SLAB UNLESS SEPARATED BY SUCH A SLAB BY AN

IMPERVIOUS MOISTURE BARRIER - WOOD SIDING, SHEATHING AND WALL FRAMING ON THE EXTERIOR OF A BUILDING LESS THAN 6" FROM

THE GROUND AREAS SUBJECT TO TERMITE INFESTATION SHALL COMPLY WITH SECTION R318

A ROUGH-FRAMED OPENING NOT LESS THAN 22"x30" W/30" MIN. HEADROOM SHALL BE PROVIDED TO ATTIC AREAS THAT HAVE A VERTICAL HEIGHT OF 30" OR GREATER (MEASURED TO THE BOTTOM OF ROOF

FRAMING MEMBERS) OVER AN AREA GREATER THAN 30SQFT MECHANICAL EQUIPMENT IN ATTICS SHALL BE PROVIDED WITH ACCESS PER SECTION M1305.1.3

FLOOR JOIST SPAN REFERENCE

R502.3.1(2) - SOUTHERN PINE #2 40psf LIVE LOAD - 20psf DEAD LOAD L/360 DEFLECTION

SIZE	SPACING	<u>SPAN</u>
	12" <i>ol</i> c	9' - 10"
2×6	16" o/c	8' - 6"
	19.2" <i>olc</i>	7' - 9"
	12" <i>ol</i> c	12' - 6"
2 × 8	16" o/c	10' - 10"
	19.2" <i>olc</i>	9' - 10"
	12" <i>olc</i>	14' - 9"
2 × 10	16" o/c	12' - 10"
	19.2" <i>ol</i> c	11' - 8"
	12" <i>olc</i>	17' - 5"
2 × 12	16" o/c	15' - 1"
	19.2" <i>ol</i> c	13' - 9"

*SPANS OVER 17' - 5" = ENGINEERED TRUSS or I-JOIST

<u> MINDOM, DOOR & GARAGE DOOR</u> HEADER SELECTION TABLE

SOUTHERN PINE #2 SUPPORTING ROOF, WALL AND FLOOR LOADS UP TO 40psf

CLEAR OPENING	MIN. HEADER SIZE
4' - 0	(2) 2 × 10
6' - 0"	(3) 2 × 12
8' - 0"	3-1/2" × 9-1/2"
10' - 0"	3-1/2" × 11-7/8"
12' - 0"	5-1/2" × 11-7/8"
16' - 0"	5-1/2" × 16"
OVER 16'	ENGINEERED
	·

MALL & HEADER STUD SELECTION TABLE

			MAX HEADER SPAN					
MFCM TAB	3	5	9	12	15	18		
SOUTHERN PINE #2			NUMBER OF JACK STUDS					
			1	2	2	2	2	
UNSUPPORTED	STUD	NUMBER OF KING STUDS						
MALL HEIGHT	SPACING	(END OF HEADER)						
10' OR LESS	12" <i>o</i> /c	2	2	3	3	3	3	
10 OK LESS	16" o/c	2	2	3	Э	3	3	
GREATER	12" <i>olc</i>	2	2	3	4	5	5	
THAN 10'	16" o/c	2	2	3	3	4	4	

CEILING JOIST SPAN REFERENCE

20psf LIVE LOAD - 10psf DEAD LOAD LIMITED STORAGE - L/240 DEFLECTION

SIZE	SPACING	<u>SPAN</u>		
	12" o/c	9' - 3"		
2×4	16" o/c	8' - 0"		
	19.2" <i>olc</i>	7' - 4"		
	12" <i>olc</i>	13' - 11"		
2×6	16" o/c	12' - 0"		
	19.2" <i>olc</i>	11' - 0"		
	12" <i>olc</i>	17' - 7"		
2×8	16" o/c	15' - 3"		
	19.2" <i>olc</i>	13' - 11"		
	12" <i>olc</i>	20' - 11"		
2×10	16" o/c	18' - 1"		
	19.2" <i>olc</i>	16' - 6"		

R802.5.1(2) - SOUTHERN PINE #2 20psf LIVE LOAD - L/240 DEFLECTION CEILING ATTACHED TO RAFTERS **SPACING** <u>SPAN</u> 13' - 6" 12" o/c 2×6 16" olc 11' - 8" 19.2" *olc* 10' - 8" 12" o/c 17' - 1"

16" o/c 19.2" o/c

12" olc

16" o/c 19.2" *olc*

12" olc

16" o/c

19.2" *olc*

 2×12

14' - 9"

13' *- 6*"

20' - 3"

17' - 6"

16' - 0"

23' - 10"


20' - 8"

18' - 10"

ROOF RAFTER SPAN REFERENCE

CLIMATIC & GEOGRAPHIC DESIGN CRITERIA - NOTE: STRUCTURAL ENGINEER TO VERIFY

GROUND SNOW	MIND	SEISMIC DESIGN	SUBJE	ECT TO DAMAGE	FROM	WINTER ICE BARRIER DESIGN UNDERLAYMENTEMP REQUIRED		FLOOD HAZARDS	AIR FREEZING	MEAN ANNUAL
LOAD	SPEED	CATEGORY	MEATHERING	FROST LINE	TERMITE				INDEX	TEMP
5	130mph	CLASS D	MODERATE	<6"	V. HEAVY	27°F	NO NO	see SURVEY	20°F	65.7°F



STRUCTURE SQUARE FOOTAGE:

1,464 SQFT FIRST FLOOR CONDITIONED SECOND FLOOR CONDITIONED 637 SQFT

2,101 SQFT TOTAL CONDITIONED

380 SQFT

151 SQFT COVERED PORCHES

COVERED PARKING/SHED


380 SQFT SCREEN PORCH

3,012 SQFT TOTAL UNDER ROOF

PROJECT RENDERING

*THIS IS A CONCEPT ONLY, NOT MEANT AS CONSTRUCTION DRAWINGS

	SHEET INDEX					
LABEL	TITLE	DESCRIPTION				
SURY	TREE & TOPOGRAPHY SURVEY					
SITE	SITE PLAN					
DRAIN	DRAINAGE PLAN					
MOB	MOBILIZATION PLAN					
A1.1	FOUNDATION PLAN					
A1.2	1ST FLOOR PLAN					
A1.3	2ND FLOOR PLAN					
A1.4	ROOF PLAN					
A2.1	STREET ELEVATION					
A2.2	MARSH ELEVATION					
E1.1	ELECTRICAL PLAN					
M1.1	HVAC PLAN					
M2.1	PLUMBING PLAN					
REND	PROJECT RENDERINGS					





SHEET COVER


MEMBER


B D


BUILDING DESIGN















FRAMING CONSTRUCTION NOTES


1) EXTERIOR WALLS: 1/2" PLYWOOD SHEATHING 0/2×4 and/or 2×6 @ 16"0/c w/ BLOCKING MIDSPAN (UNLESS




FRAMING CONSTRUCTION NOTES

5) CEILING JOISTS per ENGINEERING


- 1) EXTERIOR WALLS: 1/2" PLYWOOD SHEATHING 0/2×4 and/or 2×6 @ 16"0/c w/ BLOCKING MIDSPAN (UNLESS
- 2) INTERIOR WALLS: 2x4 and/or 2x6 @ 16"o/c w/ BLOCKING MIDSPAN (UNLESS OTHERWISE NOTED)
 3) FIRST FLOOR SYSTEM: 2x12 @ 16"o/c w/ 3/4" T&G PLYWOOD (OR EQUIVALENT), GLUED & NAILED
- 4) 2nd FLOOR SYSTEM: 2X12 @ 16"01C W/ 314" 1&G PLYWOOD (OR EQUIVALENT), GLUED & NAILED 4) 2nd FLOOR SYSTEM: 14" OPEN WEB TRUSSES (per ENGINEERING) W/ 3/4" 1&G PLYWOOD (OR EQUIVALENT), GLUED & NAILED ENGINEERED TRUSS SHOP DRAWINGS TAKE PRECEDENCE
- 6) ROOF RAFTERS: 1/2" EXT SHEATHING NAILED ON 2x10 @ 16"o/c (per ENGINEERING) w/ SIMPSON HURRICANE CLIPS
- NOTE: STRUCTURAL ENGINEERING TO TAKE PRECEDENCE FOR ALL FRAMING MEMBER SIZES, LOCATION AND PLACEMENT OF WORK DESCRIBED.





TYPICAL WALL SECTION

SCALE 1" = 1' - 0"



2nd FLOOR PLAN

SCALE 1/4" = 1' - 0"

MEMBER

A B D

AMERICAN INSTITUTE of BUILDING DESIGN

DGEWATER CONSULTING LLC
145 DATAW DRIVE
BEAUFORT, SOUTH CAROLINA 29920
www.homesbybridgewater.com

NTIAL DESIGN for MS. CONNIE KOEI LOT 471 HABERSHAM 2 BRIGHTON TRACE

11/28/2018

IOMEOWNER SIGNATURE A
DATE OF ACCEPTANCE


SHEET А1.3



HURRICANE CLIPS

- 1) EXTERIOR WALLS: 1/2" PLYWOOD SHEATHING 0/2×4 and/or 2×6 @ 16"0/c w/ BLOCKING MIDSPAN (UNLESS
- 2) INTERIOR MALLS: 2x4 and/or 2x6 @ 16"o/c w/ BLOCKING MIDSPAN (UNLESS OTHERWISE NOTED)
- 3) FIRST FLOOR SYSTEM: 2x12 @ 16"o/c w/ 3/4" T&G PLYWOOD (OR EQUIVALENT), GLUED & NAILED 4) 2nd FLOOR SYSTEM: 14" OPEN WEB TRUSSES (per ENGINEERING) w/ 3/4" T&G PLYWOOD (OR EQUIVALENT), GLUED & NAILED - ENGINEERED TRUSS SHOP DRAWINGS TAKE PRECEDENCE
- 5) CEILING JOISTS per ENGINEERING 6) ROOF RAFTERS: 1/2" EXT SHEATHING NAILED ON 2×10 @ 16"o/c (per ENGINEERING) w/ SIMPSON


NOTE: STRUCTURAL ENGINEERING TO TAKE PRECEDENCE FOR ALL FRAMING MEMBER SIZES, LOCATION AND PLACEMENT OF WORK DESCRIBED.




OPEN RAFTER RAKE DETAIL SCALE 1" = 1' - 0"

CORNICE & FASCIA DETAIL


SCALE 1" = 1' - 0"






MEMBER A B D AMERICAN INSTITUTE of BUILDING DESIGN

SHEET A1.4







TE & REVISION 1

MEMBER

BD R

AMERICAN INSTITUTE of BUILDING DESIGN


HOMEOWNER SIGNAT
DATE OF ACCEPTA


SHEEТ Е1.1

HVAC DESIGN NOTES (REF IRC 2015 PART V)

IT IS THE RECOMMENDATION OF BRIDGEWATER CONSULTING LLC THAT OUR CLIENTS USE AN INDEPENDENT MECHANICAL DESIGN SERVICE. IF THE CLIENT CHOOSES TO FORGO THE USE OF AN INDEPENDENT MECHANICAL DESIGN SERVICE, THE CLIENT SHALL INDEMNIFY BRIDGEWATER CONSULTING LLC (AND ITS OWNERS/OFFICERS/EMPLOYEES) FROM AND AGAINST ALL ALLEGATIONS, CLAIMS, ACTIONS, SUITS, DEMANDS, DAMAGES, LIABILITIES, OBLIGATIONS, LOSSES, SETTLEMENTS AND JUDGMENTS RESULTING FROM A FAILURE OF ANY FUTURE HVAC SYSTEM (TO INCLUDE DESIGN & INSTALLATION) AND ANY COLLATERAL DAMAGE INCURRED AS A RESULT.

*THE HVAC SHEETS (AND ALL M1.x LABELED SHEETS) ARE PROVIDED ONLY FOR FUTURE USE BY THE HVAC DESIGN SERVICE AND/OR HVAC CONTRACTOR AND ARE NOT PART OF THE CONTRACTUAL DESIGN AGREEMENT.





HVAC PLAN


SCALE 3/16" = 1' - 0"


MEMBER B D AMERICAN INSTITUTE of BUILDING DESIGN

PLUMBING DESIGN NOTES (REF IRC PART VI & VII)

IT IS THE RECOMMENDATION OF BRIDGEWATER CONSULTING LLC THAT OUR CLIENTS USE AN INDEPENDENT MECHANICAL DESIGN SERVICE. IF THE CLIENT CHOOSES TO FORGO THE USE OF AN INDEPENDENT MECHANICAL DESIGN SERVICE, THE CLIENT SHALL INDEMNIFY BRIDGEWATER CONSULTING LLC (AND ITS OWNERS/OFFICERS/EMPLOYEES) FROM AND AGAINST ALL ALLEGATIONS, CLAIMS, ACTIONS, SUITS, DEMANDS, DAMAGES, LIABILITIES, OBLIGATIONS, LOSSES, SETTLEMENTS AND JUDGMENTS RESULTING FROM A FAILURE OF ANY FUTURE HVAC SYSTEM (TO INCLUDE DESIGN & INSTALLATION) AND ANY COLLATERAL DAMAGE INCURRED AS A RESULT.

*THE PLUMBING SHEETS (AND ALL M2.x LABELED SHEETS) ARE PROVIDED ONLY FOR FUTURE USE BY THE PLUMBING DESIGN SERVICE AND/OR PLUMBING CONTRACTOR AND ARE NOT PART OF THE CONTRACTUAL DESIGN AGREEMENT.





PLUMBING PLAN

SCALE 3/16" = 1' - 0"

MEMBER

A

B

D

AMERICAN INSTITUTE of
BUILDING DESIGN

R CONSULTING LLC
ATAW DRIVE
OUTH CAROLINA 29920
sbybridgewater.com


AL DESIGN for MS. CONNIE KOENGE LOT 471 HABERSHAM 2 BRIGHTON TRACE

1/28/2018

DATE OF ACCEPTANCE


м2.1














MEMBER

PROJECT RENDERING

NOT TO SCALE

*THIS IS A CONCEPT ONLY, NOT MEANT AS CONSTRUCTION DRAWINGS

SHEET REND